# **CORA BIKE RACK**

## PRODUCT SPECIFICATION SHEET



# CBL SERIES CBL1 HEAVY DUTY

# BIKE LOCKER

A single door locker that provides the highest security Level A parking facility for 1 bike. Designed for quick and easy assembly. Select from several locking options. Available in galavanised or colour powder coat. Heavy duty lockers use higher specification materials and are suitable for outdoor or indoor applications.



# が か か か 1

#### Capacity

- Provides secure storage for one bicycle
- Can be mounted in a line for multiple bike installs

#### Construction

Robust construction

#### Fixings

- · Stainless steel anchor bolts fixed to ground
- Stainless steel screws for assembly

#### Finishes

- HDG steel frames
- Powder Coated 1.5mm galvanised steel panels (Cora standard colour range)
- Option powder coating of complete locker (frames and panels)

#### Assembly

 Supplied flat packed and partially assembled for full assembly and quick mounting on site

#### Locking


- Secure 3 point door locking mechanism
- Key Option supplied with individual keys for each locker door
- Latch Option allows user supplied U lock or padlock
- Electronic Option battery powered key pad

#### Compliance


• Locker is AS2890.3 (2015) compliant

# CORA BIKE RACK

## PRODUCT SPECIFICATION SHEET



#### Single locker overall dimensions



#### Bike access and storage

- · Bicycle stored securely inside locker
- · Easy access to store and remove bicycle
- · Individual locking of each installed locker
- · Locker includes internal hooks for helmet and bag hanging

## **CBL1 SERIES BIKE** LOCKER LAYOUT GUIDE


To comply with AS2890.3 (2015) minimum 2000mm aisle spacing between lockers or to wall or obstructions is required.


For specific assembly and installation instructions relating to CBL Series lockers, please refer to individual instruction information sheets.

Lockers should not be installed, based on the information on this sheet alone.





Lockers can be installed either as a single locker or next to each other in rows, in multiples as required





Minimum 2000mm aisle spacing between lockers





Minimum 2000mm aisle spacing between lockers and wall or obstructions











PH 1800 249 878

sales@cora.com.au www.cora.com.au