CORA BIKE RACK

PRODUCT SPECIFICATION SHEET



CBL SERIES CBL1 LIGHT DUTY BIKE LOCKER

A single door locker that provides the highest security Level A parking facility for 1 bike. Select from several locking options. This is a light duty version of the original CBL. Light duty lockers are suitable for indoor applications to reduce costs.



Capacity

- Provides secure storage for one bicycle
- Can be mounted in a line for multiple bike installs

Construction

Light duty

Fixings

- Stainless steel anchor bolts fixed to ground
- Stainless steel screws for assembly

Finishes

- HDG steel frame
- 1.0mm galvanised steel panels
- Option powder coated panels (on request)

Assembly

 Supplied flat packed and partially assembled for full assembly and mounting on site

Locking

- Secure 3 point door locking mechanism
- Key Option supplied with individual key for each locker door
- User Option "u lock" or padlock option


Compliance

• Locker is AS2890.3 (2015) compliant





CORA BIKE RACK


PRODUCT SPECIFICATION SHEET



Single locker overall dimensions







Bike access and storage

- · Bicycle stored securely inside locker
- · Easy access to store and remove bicycle
- · Individual locking of each installed locker
- · Locker includes internal hooks for helmet and bag hanging
- · Optional bicycle wheel track also available

CBL1 SERIES BIKE LOCKER LAYOUT GUIDE


To comply with AS2890.3 (2015) minimum 2000mm aisle spacing between lockers or to wall or obstructions is required.


For specific assembly and installation instructions relating to CBL Series lockers, please refer to individual instruction information sheets.

Lockers should not be installed, based on the information on this sheet alone.


Single or Multiple install of lockers


Lockers can be installed either as a single locker or next to each other in rows, in multiples as required





Minimum 2000mm aisle spacing between lockers





Minimum 2000mm aisle spacing between lockers and wall or obstructions









PH 1800 249 878

sales@cora.com.au www.cora.com.au